

Varifocal Dome Camera (3-axis, HQ1)

Products List > D Series > Camera > Varifocal Dome Camera (3-axis, HQ1) > MTC-2438HODN3X

MTC-2438HODN3X



MTC-2438HODN3X

FEATURES



3-Axis Gimbal Mechanism Option:



MTB-201



Wall Mount




MTB-503



Ceiling Mount

MTC-2438HODN3X

- ◆ 1/3" Super Hi-Res. Color Camera
- ◆ Sony HQ1, 540TVL, 0.15Lux@F1.2
- ◆ AGC / BLC / FL / Digital Day&Night (ON/OFF)
- ◆ Color Mode Switches to B/W Mode
- ◆ 12Vdc, 12Vdc/24Vac (Option)
- ◆ Unique 3-axis Gimble Mechanism
- ◆ Built-in DNR & Sense Up



12Vdc±10%

Option: Dual Voltage



Tol:±0.5 Unit:mm

SPECIFICATIONS

MTC-2438HODN3X		
TV System	PAL	NTSC
Image Sensor	1/3" Sony Super HAD CCD II	
Number of Total Pixels	795(H)x596(V)	811(H)x508(V)
Resolution ; DSP	540TVL ; Sony HQ1	
Minimum Illumination	0.15Lux@F1.2	
Video Output ; Connector	1.0Vp-p Composite, 75Ω (BNC)	
Signal to Noise Ratio	More than 50dB (AGC off)	
Gamma Correction	0.45	
Synchronizing System	Internal	
Automatic Electronic Shutter	Automatic, 1/50(60)~1/100,000 sec.	
Automatic Gain Control	ON / OFF	
Automatic White Balance	Automatic	
Back Light Compensation	ON / OFF	
Flickerless	ON / OFF	
DNR ; Sense Up	Automatic Dynamic Digital Noise Reduction (DNR) ; Automatic	
Digital Day&Night Mode	COLOR / D&N (B/W Mode<2Lux, Color Mode>5Lux)	
Automatic IRIS	DC	
Adjustment VR	DC Level	
Lens Mount	Built-in DC Auto IRIS Lens	
Lens, Angle of View(H)	Standard:f2.8mm~10mm/F1.2 Aspherical Auto IRIS Lens/94.6°~28.8° Option:f2.5mm~6.0mm/F1.3 Aspherical Auto IRIS Lens/108.2°~47.6°	
Power Supply ; Consumption	Standard:12Vdc±10%, Option:12Vdc/24Vac (10.8~39Vdc/24Vac) ; 2.0 W	
Operation ; Storage Temp.	-10°C~50°C ; -20°C~60°C	
Operation ; Storage Humidity	Maximum: RH80% ; RH90%	
Dimensions	124(DIA)x102(H)mm	
Net Weight	12Vdc±10%:320g, 12Vdc/24Vac:380g	
Accessories Option (Page)	Wall Bracket: MTB-201(I-4), MTB-503	