

HQ1 Vandalproof Camera (3-axis)

Products List > D Series > Vandalproof Camera > HQ1 Vandalproof Camera (3-axis) > MTC-5838HQDN

MTC-5838HQDN

MTC-5838HQDN



FEATURES

3D Free Rotation





3D Free Rotation (3-axis)

Bracket Option:




MTC-5838HQDN

- ◆ 1/3" Super Hi-Res. Vandalproof Camera
- ◆ Sony HQ1/ 540TVL/ 0.15Lux@F1.2
- ◆ Digital D&N/AGC/BLC/F.L (ON/OFF)
- ◆ Automatic Dynamic Digital Noise Reduction (DNR); Sense Up
- ◆ Built-in Varifocal Lens
- ◆ Water Resistance: IP66
- ◆ Breaking Strength: 656.1Kgf
- ◆ Unique 3-Axis Gimble Mechanism
- ◆ Option: Heater; Dual Voltage; Metal Fittings



Option: Metal Fittings



Option: Dual Voltage (AC24/DC12)



Option: Heater



Tol: ±0.5 Unit:mm

SPECIFICATIONS

	MTC-5838HQDN	
	PAL	NTSC
TV System	PAL	NTSC
Image Sensor	1/3" Sony Super HAD CCD II	
Number of Total Pixels	795(H)x596(V)	811(H)x508(V)
Resolution ; DSP	540TVL ; Sony HQ1	
Minimum Illumination	0.15Lux@F1.2	
Video Output ; Connector	1.0Vp-p Composite, 75Ω ; BNC	
Signal to Noise Ratio	More than 48dB (AGC off)	
Gamma Correction	0.45	
Mechanical IR Cut Filter (ICR)	NA	
IR LED ; Working Distance	NA	
Synchronizing System	Internal	
Automatic Electronic Shutter	ON: 1/50(60)sec.~1/100,000sec. / OFF: 1/50(60)sec.	
Automatic Gain Control	ON / OFF	
Automatic White Balance	Automatic	
Back Light Compensation	ON / OFF	
Flickerless	ON / OFF	
DNR ; Sense Up	Automatic Dynamic Digital Noise Reduction (DNR) ; Automatic	
Digital Day&Night Mode	COLOR / D&N (B/W Mode<2Lux, Color Mode>5Lux)	
Automatic IRIS	DC	
Adjustment VR	DC Level	
Lens Mount	Built-in DC Auto IRIS Lens	
Lens, Angle of View(H)	Standard: f2.8mm~10mm/F1.2 Aspherical Auto IRIS Lens/94.6°~28.8° Option: f9mm~22.0mm/F1.5 Auto IRIS Lens/29.2°~13.0°	
Water Resistance	IP66	
Max. Breaking Strength	656.1 Kgf	
Power Supply ; Consumption	12Vdc±10%, Option:10.8~39Vdc/24Vac ; 2.3W(Heater on:6.0W)	
Operation ; Storage Temp.	-10°C~50°C ; -20°C~60°C	
Operation ; Storage Humidity	Maximum: RH80% ; RH90%	
Dimensions	140(DIA)x112(H)mm	
Net Weight	950g	
Accessories Series Option(Page)	Wall Bracket: MTB-413 ; Ceiling Bracket: MTB-504 ; Thread Metal Flexible Conduit Fittings: S-FZS26	