

Vandalproof 3-axis OSD Camera

Products List > D Series > Vandalproof Camera > Vandalproof 3-axis OSD Camera > MTC-L5938

MTC-L5938

MTC-L5938



FEATURES



Mechanical IR Cut Filter (ICR)

3D Free Rotation (3-axis)

Bracket Option:



MTB-413 Wall Mount

MTB-504 Ceiling Mount



Light Module



MTC-L5938

- ◆ Excellent Super-high Resolution Technology (CCD)
- ◆ Color Mode: 540TVL; B/W Mode: 650TVL
- ◆ 0 Lux (IR LEDs on at 2 Lux)
- ◆ Water Resistance: IP66 ; Breaking Strength: 656.1Kgf
- ◆ Built-in Varifocal Lens & Unique 3-Axis Gimble Mechanism
- ◆ OSD Setting Menu & Mirror/ Vertical/ Rotate Function
- ◆ Motion Detection Function Supported
- ◆ Privacy Masking (4 Programmable Zones)
- ◆ High Sensitivity with Day-Night Function
- ◆ Built-in Dynamic Noise Reduction & Sense-up
- ◆ Option: Heater; Metal Fittings

Built-in OSD Controller



Option: Metal Fittings



10.8~39Vdc/24Vac Dual Voltage (AC24/DC12)



Option: Heater



Tol: ±0.5 Unit:mm

SPECIFICATIONS

MTC-L5938		
	PAL	NTSC
TV System	PAL	NTSC
Image Sensor	1/3" Sony Super HAD CCD II	
Number of Total Pixels	795(H)x596(V)	811(H)x508(V)
Resolution	Color: 540TVL, B/W: 650TVL	
Minimum Illumination	0 Lux	
Video Output	1.0Vp-p Composite, 75Ω ; BNC	
Signal to Noise Ratio	More than 50dB (AGC OFF, Weight ON)	
Gamma Correction	0.45	
Mechanical IR Cut Filter (ICR)	Automatically Switches (B/W Mode<2Lux, Color Mode>5Lux)	
IR LED ; Working Distance	30 units (IR LEDs on<2Lux, IR LEDs off>5Lux) ; Outdoor:15m	
Menu	OSD Control	
Title	TITLE / LOCATION	
Synchronizing System	INTERNAL / LINE LOCK	
Automatic Electronic Shutter	ON:1/50(60)sec~1/120,000sec. / Manual: 1/50(60) sec. FL 1/120(100)sec. 1/250sec. 1/500sec. 1/1000sec. 1/2000sec. 1/4000sec. 1/10000sec.	
Automatic Gain Control	LOW / MIDDLE / HIGH / OFF	
White Balance	ATW / AWC / MANUAL (2600°K~9200°K)	
Back Light Compensation	LOW / MIDDLE / HIGH / OFF	
Flickerless	Manual Electronic Shutter = FL 1/120(100)sec.	
Dynamic Noise Reduction	Automatic	
Sense Up	NORMAL, x2, x4, x8, x16, x32	
Digital Day&Night Mode	AUTO / COLOR / B&W / EXT (CDS)	
Mirror Mode	NORMAL / MIRROR / VERTICAL / ROTATE	
Motion Detection ; Privacy	ON / OFF (48 Zones) ; ON / OFF (4 Programmable Zones)	
Automatic IRIS	DC	
Lens Mount	Built-in DC Auto IRIS Lens	
Lens, Angle of View(H)	f2.8mm~10mm/F1.2 Aspherical Auto IRIS Lens/94.6°~28.8°	
Water Resistance	IP66	
Max. Breaking Strength	656.1 Kgf	
Power Supply ; Consumption	10.8~39Vdc/24Vac ; 3.0W	
Operation ; Storage Temp.	-10°C~50°C ; -20°C~60°C	
Operation ; Storage Humidity	Maximum:RH80% ; RH90%	
Dimensions	140(DIA)x112(H)mm	
Net Weight	960g	
Accessories Series Option(Page)	Wall Bracket: MTB-413 ; Ceiling Bracket: MTB-504 ; Thread Metal Flexible Conduit Fittings: S-FZS26	