

High Speed Dome Outdoor Camera (Bracket Mount)

Products List > B Series > Speed Dome Camera > High Speed Dome Outdoor Camera (Bracket Mount) > MZC-91IR36DN

MZC-91IR36DN

FEATURES


Mechanical IR Cut Filter (ICR)
MZC-91IR36DN



MZC-91IR36DN



Option:



MTB-901A, MTB-901B
Outdoor Ceiling Mount



MTB-902
Outdoor Wall Mount




MTB-904
Pole Mount



MTB-905
Corner Mount

MZC-91IR36DN

- ◆ 1/4" 36x Outdoor Speed Dome Camera
- ◆ Built-in Sony Exview-HAD CCD
- ◆ Color:540TVL, B&W:560TVL, 0.7Lux@F1.6
- ◆ Mechanical IR Cut Filter
- ◆ With Home Function
- ◆ Time Clock available
- ◆ Restore the system automatically after power failure



Tol:±0.5 Unit:mm

SPECIFICATIONS

| | | MZC-91IR36DN | |
|--------------------------------|--|--|----------------|
| | | PAL | NTSC |
| TV System | | PAL | NTSC |
| Image Sensor | | 1/4" Sony Exview-HAD CCD | |
| Number of Total Pixels | | 470,000 Pixels | 410,000 Pixels |
| Resolution | | Color:540TVL, B/W:560TVL | |
| Minimum Illumination | | Color:0.7Lux, B/W:0.1Lux@F1.6 | |
| Wide Dynamic Range | | NA | |
| Video Output | | 1.0Vp-p Composite, 75Ω (BNC) | |
| Signal to Noise Ratio | | More than 50dB | |
| Gamma Correction | | 0.45 | |
| Mechanical IR Cut Filter (ICR) | | Automatically Switches (Switching Lux Level Can Be Adjusted, 15 steps) | |
| Menu | | OSD by RS485 Control | |
| Electronic Shutter | | AUTO 1/50(60)~10,000 sec., 9steps | |
| Automatic Gain Control | | Automatic | |
| White Balance | | AUTO / ATW / One Push / Manual / INDOOR / OUTDOOR | |
| Back Light Compensation | | ON / OFF | |
| Flickerless | | ON / OFF | |
| Language | | English, Traditional/Simplified Chinese, Japanese | |
| E-Zoom | | NA | |
| Alarm-In ; Alarm-Out | | 4 In, 1 Out | |
| Automatic IRIS, Focus | | Automatic | |
| Lens | | 36x zoom f=3.4~122.4mm/57.8°~1.7° | |
| Camera Control Interface | | RS485 Interface OSD Control by Pelco-D, Pelco P | |
| Controls | | PAN / TILT, LENS | |
| Auto Pan | | Yes | |
| Tour Pattern | | 1 Group (accommodates preset #1~#10) | |
| Home Function | | Yes | |
| System Memory | | Yes | |
| Panning Range & Speed | | 360°Continuous ; 0.2°~240°/sec. | |
| Tilt Range & Speed | | 0°~90° ; 0.2°~120°/sec. | |
| Pan, Tilt Accuracy | | ±0.02° | |
| Preset Positions | | 128 Positions | |
| Water Resistance | | IP66 | |
| Power Supply ; Consumption | | 24Vdc/24Vac ; 25W (45W,When the Optional Heater is on) | |
| Operation ; Storage Temp. | | 0°C~50°C ; -10°C~60°C | |
| Operation ; Storage Humidity | | Maximum:RH80% ; RH90% | |
| Dimensions | | 290(DIA)x293(H)mm | |
| Net Weight | | 4,050g | |
| Accessories Option (Page) | | MTB-901A, MTB-901B, MTB-902, MTB-904, MTB-905 (see the above images) | |